



MECHANICAL GAS SAVERS

The Carlisle Mechanical Gas Savers allow the operator to hang a torch from the arm, shutting off the gas flow to the torch and therefor saving gas when the torch is not needed. Models are available with a pilot flame on the unit so that the torch can easily be relit when needed. Depending on the model selected, Carlisle Mechanical Gas Savers can be used with natural gas, propane, butane, methane, acetylene, or mixed gases and oxygen, air, or water.

The Mechanical Gas Savers are available in four different models. The first model is the W-101-E. The W-101-E is used with Acetylene. The model W-102-EI is used for inert arc welding operations. This model allows for positive shutoff of both gas and water and is not available with a standing pilot. The model W-103-ELP is specifically setup to run with Natural Gas. The W-104-P is used with propane at 4psi or more. This unit uses special seals that are designed for use with propane gas.



W-101-E Mechanical Gas Saver
28B001-0000

BULLETIN REFERENCES

Safety- Bulletins 18A, 18B
Other Controllers- Bulletins 16F, 28A
Hand Torches- Bulletins 22A, 22B, 22C, 22D 22E

CATALOG	MODEL
28B001-0000	W-101-E
28B002-0000	W-102-EI
28B003-0000	W-103-ELP
28B004-0000	W-104-P

Carlisle Machine Works, Inc.,
P.O. Box 746, 412 S. Wade Blvd., Bldg. #5, Millville, NJ 08332
Phone: (800) 922 - 1167 Fax: (856) 825 - 5510
Web Site: www.carlislemachine.com E-Mail: carlisle@carlislemachine.com

